## EXP40

Expansion Module for the SIP-T46GN and SIP-T48GN Expanding the functional capability of the above phones Large graphic LCD

Two pages of 20 flexible buttons

Program up to 40 various features

Adjustable stand with two angles

Wall mountable



### **High-Performance LCD Expansion Module**

The EXP40 is designed to match the stylish look and feel of T46G and T48G with rubber feet and new foot stand allowing two positions for the device, as well as wall mountability. The backlit display eliminates the need for external light. The unit is easy to install, simply link EXP40 to the EXT port of the phone

Equipped with a 160x320 graphic LCD with Backlight, 20 physical keys each with a dual-color LED and two page views are possible. This allows 40 additional programmable keys that can be used for speed dialing, BLF/BLA, call forward, transfer, park, pickup, etc. Two independent control keys are used for fast switch between pages.

As an attendant console application up to 6 expansion modules can be supported adding up to 240 additional buttons. More than two connections must be powered by a conventional power supply (5V/1.2A).





# EXP40

#### Display

- > 160x320 graphic LCD with 16-level grayscales
- > LCD Backlight
- > Two page views are possible
- > Different icons for each function shown on the LCD

#### Features Keys and Indicator

- > 20 physical keys each with a dual-color LED
- > 20 additional keys through page switch
- > 2 independent control keys are used for fast switch pages
- > Programmable for shared line, BLF List, call park, conference, forward, group pickup, group listening, LDAP, Pick UP, XML Browser

Physical Feature

- > Wall mountable
- > Stand with 2 adjustable angles
- > Expansion module (≤2) is powered by the host phone
- > Supports up to 6 modules daisy-chain
- > 2xRJ12 (6P6C) ports for data in and out
- > Dimension (W\*D\*H\*T): 127mm\*213mm\*167mm\*45mm
- > Applies to Yealink IP Phone
- > Operating temperature: -10~50°C
- > Operating humidity: 10-95%

#### Package Features

> Qty/CTN: 10 PCS

> N.W/CTN: 6.7 kg

> G.W/CTN: 7.6 kg

> Giftbox size: 237mm\*154mm\*100mm

> Carton Meas: 520mm\*317mm\*247mm

#### Certifications

**WEEE Compliant** 



**ROHS Compliant** 













...and many more



www.rfcnet.com / www.rfcvoip.com 866-RFC-NET9 - sales@rfcnet.com